


## Serie Sliding

# 328B Nylon Sliding Cable Chain with un-screwable aluminium rods

### Inner height (D) 48 mm

Strong double share Sideband & Frame construction with large anti-friction triple-pin. The chain incorporates large sliding-skid surfaces to offer durability, even with high speed/loads. The Alu-rod frames are un-screwable from inner and outer radius. As standard the chain comes with frames every second link, on request with frames every link. Separator systems are available.



Separator	
- Unassembled	Part.no S3000F
- Assembled	Part.no S3000FMC
Pin	
	Part.no PG328TP

### Technical characteristics

Speed	3.5 m/s
Acceleration	8 m/s <sup>2</sup>


For higher requirements please consult our technical dept.

A	B	C	D	R	Weight/m	Chain
mm	mm	mm	mm	mm	kg	Part Number
162	79	100	48	150-180-200-230-280-400	2.50	328B100 □□□*
212	79	150	48	150-180-200-230-280-400	2.60	328B150 □□□*
262	79	200	48	150-180-200-230-280-400	2.75	328B200 □□□*
312	79	250	48	150-180-200-230-280-400	2.90	328B250 □□□*
362	79	300	48	150-180-200-230-280-400	3.00	328B300 □□□*
C+62	79	.....	48	150-180-200-230-280-400		328B □□□□□**

\*Complete the code by inserting the value of the radius (R); Ex. 328B100 □□□□

\*\*Complete the code by inserting the value of the quote C and the radius (R); Ex. 328B □□□□□□□□

Chain equipped with aluminium rods every pitch: complete the code by inserting the letter D.  
Ex. 328B100150 □



Length of chain (L)  
Half travel distance ( $\frac{LS}{2}$ )  
plus length of curve (M)  
 $L = \frac{LS}{2} + M$

R	H	N	M
mm	mm	mm	mm
150	379	425	955
180	439	530	1220
200	479	600	1395
230	539	700	1655
280	639	875	2095
400	879	1285	3145



Version with Alu-rods on every second pitch.

### End Brackets

The end brackets set allows the two ends of the chain to be attached to the equipment. One set includes two pivoting end brackets to be installed at the moving point and two standard steel end brackets to be installed at the fixed point.

**Bright Zinc Plated Steel Movable Type\*\*\*** (moving point)  
**Bright Zinc Plated Steel Type\*\*\*** (fixed point)





Fig. A  
Chain fixed outside the radius. (Fig. A)



Chain Type	F mm
328B100	87
328B150	137
328B200	187
328B250	237
328B300	287

Special widths F=A-75

### Bright Zinc Plated Steel Type Part Numbers

Complete Set Assembled Chain	End Brackets	Type	Set
328B...	A328KM		


Complete Set Unassembled Chain	End Brackets	Type	Set
328B...	A328K		

\*\*\* Available on request in stainless steel




## Serie Sliding

# 328B Nylon Sliding Cable Chain with un-screwable aluminium rods



Supplementary movable separators.



Steel lamina cover.

Special tool to remove the connecting pivots:  
Part Number F2038.



For further information please consult Brevetti Stendallo's Technical Office